

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims**

1. (Currently Amended) A method for providing information describing a file system connection between a local file system located on a local system and a host file system located on a host system, said method comprising:

encoding a local system data structure comprising at least one tag representing the local file system;

encoding a host system data structure comprising at least one tag representing the host file system; and

encoding a mapping data structure comprising at least one tag representing a mapping between a file in the local file system and a file in the host file system and a transfer type that defines a data format for transferring data between the host system and the local system to support remote editing of files in the host file system from the local file system, wherein the tags are in a metalanguage format, and wherein each tag has an identifier and a set of one or more attributes and wherein the encoded local system data structure, host system data structure, and mapping data structure forms a file system connection descriptor; and

using the file system connection descriptor to access the host file indicated in the mapping data structure by using the mapping data structure to determine a pattern describing a host file system type that maps to a local file system type, wherein the transfer type for the pattern defines how data is transferred between a host file of the host file system type having the determined pattern to the local file system in which the local file system type applies.

2-8. (Canceled)

9. (Currently Amended) The method of claim 1, wherein the local file system type comprises a local file extension, wherein the mapping data structure comprises:

a local file extension data structure storing [[a]] the local file extension for each mapping;

a host file pattern data structure storing [[a]] the pattern for each mapping describing a host file to which the local file extension will be applied.

10. (Previously Presented) The method of claim 9, wherein the mapping data structure further comprises:

a host codepage data structure storing an identification of a host codepage in which data in the host file is encoded; and

a local-codepage data structure storing an identification of a local codepage in which data in a local file is encoded.

11. (Previously Presented) The method of claim 1, wherein the host system data structure comprises:

a data structure storing an identification of the host system;

a data structure storing an identification of a user of the host system;

a data structure storing an identification of a preferred drive on the local system; and

a data structure storing an indication that the preferred drive be automatically connected by default when a remote connection is established with the host system.

12. (Previously Presented) The method of claim 1, wherein the host system data structure further comprises:

a data structure storing an identification of a list of qualifier data structures, wherein each qualifier data structure stores a qualifier name, a name identifying a directory on the host system, and an identification of file attributes of a file located in the host system directory.

13. (Previously Presented) The method of claim 1, wherein the file system connection descriptor is encoded in a tagged metalanguage document comprising one or more tags, each tag having an identifier and a set of one or more attributes.

14. (Previously Presented) The method of claim 13, wherein the tagged metalanguage is Extensible Markup Language (XML).

15-21. (Canceled)

22. (Previously Presented) The method of claim 1, wherein a first transfer type indicates to transfer one file unmodified between the host file system and the local file system and wherein a second transfer type indicates to translate text in the file to transfer from the host file system to the local file system.

23. (Previously Presented) The method of claim 22, wherein the first transfer type comprises a binary transfer type and wherein the second transfer type comprises a text transfer type.

24. (Previously Presented) The method of claim 22, wherein a host and local code pages are used to translate text for the text transfer type.

25-30. (Canceled)

31. (New) A system for providing information describing a file system connection between a local file system located on a local system and a host file system located on a host system, said method comprising:

- a processor;

- a computer usable media including code executed by the processor to perform operations, the operations comprising:

- encoding a local system data structure comprising at least one tag representing the local file system;

- encoding a host system data structure comprising at least one tag representing the host file system; and

- encoding a mapping data structure comprising at least one tag representing a mapping between a file in the local file system and a file in the host file system and a transfer type that defines a data format for transferring data between the host system and the local system to support remote editing of files in the host file system from the local file system, wherein the tags are in a metalanguage format, and wherein each tag has an identifier and a set of one or more attributes and wherein the encoded local system data

structure, host system data structure, and mapping data structure forms a file system connection descriptor; and

using the file system connection descriptor to access the host file indicated in the mapping data structure by using the mapping data structure to determine a pattern describing a host file system type that maps to a local file system type, wherein the transfer type for the pattern defines how data is transferred between a host file of the host file system type having the determined pattern to the local file system in which the local file system type applies.

32. (New) The system of claim 31, wherein the local file system type comprises a local file extension, wherein the mapping data structure comprises:

- a local file extension data structure storing the local file extension for each mapping;
- a host file pattern data structure storing the pattern for each mapping describing a host file to which the local file extension will be applied.

33. (New) The system of claim 32, wherein the mapping data structure further comprises:

- a host codepage data structure storing an identification of a host codepage in which data in the host file is encoded; and
- a local-codepage data structure storing an identification of a local codepage in which data in a local file is encoded.

34. (New) The system of claim 31, wherein the host system data structure comprises:

- a data structure storing an identification of the host system;
- a data structure storing an identification of a user of the host system;
- a data structure storing an identification of a preferred drive on the local system; and
- a data structure storing an indication that the preferred drive be automatically connected by default when a remote connection is established with the host system.

35. (New) The system of claim 31, wherein the host system data structure further comprises:

a data structure storing an identification of a list of qualifier data structures, wherein each qualifier data structure stores a qualifier name, a name identifying a directory on the host system, and an identification of file attributes of a file located in the host system directory.

36. (New) The system of claim 31, wherein the file system connection descriptor is encoded in a tagged metalanguage document comprising one or more tags, each tag having an identifier and a set of one or more attributes.

37. (New) The system of claim 36, wherein the tagged metalanguage is Extensible Markup Language (XML).

38. (New) The system of claim 31, wherein a first transfer type indicates to transfer one file unmodified between the host file system and the local file system and wherein a second transfer type indicates to translate text in the file to transfer from the host file system to the local file system.

39. (New) The system of claim 38, wherein the first transfer type comprises a binary transfer type and wherein the second transfer type comprises a text transfer type.

40. (New) The system of claim 38, wherein a host and local code pages are used to translate text for the text transfer type.

41. (New) A computer program product comprising a computer useable medium including code executed by a processor for providing information describing a file system connection between a local file system located on a local system and a host file system located on a host system, wherein the code is executed to perform operations, the operations comprising:  
encoding a local system data structure comprising at least one tag representing the local file system;  
encoding a host system data structure comprising at least one tag representing the host file system; and

encoding a mapping data structure comprising at least one tag representing a mapping between a file in the local file system and a file in the host file system and a transfer type that defines a data format for transferring data between the host system and the local system to support remote editing of files in the host file system from the local file system, wherein the tags are in a metalanguage format, and wherein each tag has an identifier and a set of one or more attributes and wherein the encoded local system data structure, host system data structure, and mapping data structure forms a file system connection descriptor; and

using the file system connection descriptor to access the host file indicated in the mapping data structure by using the mapping data structure to determine a pattern describing a host file system type that maps to a local file system type, wherein the transfer type for the pattern defines how data is transferred between a host file of the host file system type having the determined pattern to the local file system in which the local file system type applies.

42. (New) The computer program product of claim 41, wherein the local file system type comprises a local file extension, wherein the mapping data structure comprises:

- a local file extension data structure storing the local file extension for each mapping;
- a host file pattern data structure storing the pattern for each mapping describing a host file to which the local file extension will be applied.

43. (New) The computer program product of claim 42, wherein the mapping data structure further comprises:

- a host codepage data structure storing an identification of a host codepage in which data in the host file is encoded; and
- a local-codepage data structure storing an identification of a local codepage in which data in a local file is encoded.

44. (New) The computer program product of claim 41, wherein the host system data structure comprises:

- a data structure storing an identification of the host system;
- a data structure storing an identification of a user of the host system;
- a data structure storing an identification of a preferred drive on the local system; and

a data structure storing an indication that the preferred drive be automatically connected by default when a remote connection is established with the host system.

45. (New) The computer program product of claim 41, wherein the host system data structure further comprises:

a data structure storing an identification of a list of qualifier data structures, wherein each qualifier data structure stores a qualifier name, a name identifying a directory on the host system, and an identification of file attributes of a file located in the host system directory.

46. (New) The computer program product of claim 41, wherein the file system connection descriptor is encoded in a tagged metalanguage document comprising one or more tags, each tag having an identifier and a set of one or more attributes.

47. (New) The computer program product of claim 46, wherein the tagged metalanguage is Extensible Markup Language (XML).

48. (New) The computer program product of claim 41, wherein a first transfer type indicates to transfer one file unmodified between the host file system and the local file system and wherein a second transfer type indicates to translate text in the file to transfer from the host file system to the local file system.

49. (New) The computer program product of claim 48, wherein the first transfer type comprises a binary transfer type and wherein the second transfer type comprises a text transfer type.

50. (New) The computer program product of claim 48, wherein a host and local code pages are used to translate text for the text transfer type.